## Auxiliary Power and Grounding Transformers

Complete the Package



LV	3kVA-300kVA	MV
Primary voltages: 480 / 600 / 800VAC single or three phase		Primary voltages: up to 34.5kV single or three phase
Secondary voltages: 120/240 single phase; 208/480 three phase		
Dual secondary options		
NEMA 3R, rack or padmount		NEMA 3R, padmount
Secondary panelboard / load centers		





LV / 20KVA POWEF CENTE 600:120 240 1P

## LV & MV Grounding Transformers and Reactors

- ·480VAC up to 34.5kV
- ·Single phase & three phase, 1kVA up to 4500kVA
- ·Full 3D design
- ·NEMA 3R padmount





NGR: 6.25 KVAR, 10 OHMS



NGR: 30 KVAR, 15KV CLASS

## **NEW PRODUCT**

## Modular SWBD

(estimated to ship 4Q 2024)

- Designed from ground up for BESS / Solar / EV Charging Applications
- Multiple main sections (M-T-M, GenSET), 5000A (6000A air cooled)
- Direct bus connection or cable connection to MVT

- · Multiple feeder sections with feeder sizes up to 2500A
- ·NEMA 3R, multi-section design
- ·Seismic ratings

ASK OUR SALES TEAM FOR DETAILS

2025 Product Portfolio Page 8